

S - SERIES WATER-COOLED* SINGLE-STAGE

Dimensions and Specifications *Typical, do not use for construction. (Drawings are provided with order acknowledgement.)*

Model	Motor HP	Max. Pressure PSIG	Free Air ** Delivery CFM	Length In.	Width In.	Height In.	Net Weight Lbs.
KNW0-A/S	30	35	178	69	49	53	3420
KNW0-B/S	40	35	228	69	49	53	3490
KNW0-C/S	50	35	298	69	49	53	3630
KNW0-D/S	60	35	338	69	49	53	3660
KNW1-A/S	60	35	421	83	62	60	5270
KNW1-B/S	75	35	511	83	62	60	5620
KNW1-C/S	75	35	540	83	62	60	5620
KNW1-D/S	100	35	626	83	62	60	5870
KNW1-E/S	100	35	661	83	62	60	5870
KNW1-F/S	100	35	736	83	62	60	5910
KNW2-A/S	125	35	921	124	74	72	8820
KNW2-B/S	150	35	1108	124	74	72	8860
KNW2-C/S	200	35	1322	124	74	72	9110
KNW2-D/S	200	35	1565	124	74	72	9880

*For air-cooled requirements refer to bulletin KNWA/S

**Capacity at 35 PSIG

