



H-SERIES AIR-COOLED* TWO-STAGE

60 HZ

Dimensions and Specifications *Typical, do not use for construction. (Drawings are provided with order acknowledgement.)*

Model	Motor HP	Max. Pressure PSIG	Free Air** Delivery CFM	Length In.	Width In.	Height In.	Net Weight Lbs.
KNWA00-A/H	25	125	72	67	40	60	2340
KNWA00-B/H	30	125	91	67	40	60	2360
KNWA00-C/H	40	125	122	67	40	60	2380
KNWA00-D/H	50	125	162	67	40	60	2390
KNWA00-E/H	60	125	201	67	40	60	2650
KNWA0-A/H	50	150	172	69	50	67	3670
KNWA0-B/H	60	150	223	69	50	67	3740
KNWA0-C/H	75	150	292	69	50	67	3880
KNWA0-D/H	100	135	331	69	50	67	3910
KNWA1-A/H	100	150	413	100	63	74	5620
KNWA1-B/H	125	150	504	100	63	74	5970
KNWA1-C/H	125	150	534	100	63	74	5970
KNWA1-D/H	150	150	618	100	63	74	6220
KNWA1-E/H	150	150	653	100	63	74	6220
KNWA1-F/H	200	135	728	100	63	74	6460
KNWA1-G/H	200	135	812	100	63	74	6460
KNWA2-A/H	200	150	908	124	75	110	10000
KNWA2-B/H	250	150	1096	124	75	110	10200
KNWA2-C/H	300	150	1310	124	75	110	11000
KNWA2-D/H	350	150	1552	124	75	110	11600

For water cooled requirements, refer to Bulletin KNW/L & KNW/H



Standard Equipment and Safety Devices

Controls and Instrumentation

Service Indicators

- Air inlet filter condition indicator
- Oil filter condition indicator
- Oil level gauge
- Routine maintenance

Pressure Indicators

- First stage air discharge pressure
- Second stage air discharge pressure
- Oil pressure

Temperature Indicators

- First stage air discharge
- Second stage air inlet
- Second stage air discharge
- Lube oil
- Compressor discharge temperature

Additional Indicators

- Stand-by mode light
- Oil pump run light
- Fan run light
- Compressor run light
- Compressor load light
- Alarm light
- Hour meter – running time
- Hour meter – loaded time
- Manual unload light and switch
- Pre alarms

Safety Devices

All safety shutdowns, indicated by message on display and alarm light

- Compressor motor overload shutdown light
- Oil pump motor overload shutdown light
- Fan motor overload shutdown light
- High first stage air discharge temperature shutdown and light
- High second stage suction temperature shutdown and light
- High second stage air discharge temperature shutdown and light
- High oil temperature shutdown and light
- Low oil pressure shutdown and light
- High cabinet temperature shutdown and light

- Starter failure light
- Temperature pre-shutdown alarms
- Compressor discharge temperature shutdown and alarm

Additional Devices

- Start/stop push buttons
- Lamp test
- Audible alarm
- Acknowledge switch
- Reset switch
- Common alarm contacts for remote indication
- Event alarm log
- Internet options
- Color monitor options

Additional Features

Packaged Assembly

- Air-cooled or water cooled
- Integral air-cooled or water-cooled aftercooler with moisture separator and automatic drain
- Cabinet ventilating fan
- Easy access for maintenance
- Removable doors
- Low installation cost
- Few connections required for installation – compressed air, condensate drains, electrical and water (when required)
- Wye Delta motor starter (460 volt standard)
- CSA certified panel



Advanced Design

- Super Rotor delivers more cfm per horsepower
- Patent numbers 4583927 & 4671749

Efficient Control

- Load/unload electro-pneumatic
- Low unload horsepower

Vibration Free

- No vibration generated in rotary design
- No special foundation required
- Variable frequency drive available
- Energy saving heat of compression dryer available

Standard and optional equipment subject to change without notice.

DISTRIBUTED BY:

ROGERS
MACHINERY
COMPANY, INC.

KOBELCO
KNW SERIES

14650 SW 72nd Avenue
Portland, Oregon 97224-7943
P.O. Box 230429
Portland, Oregon 97281-0429
Phone (503) 639-0808
Fax (503) 639-0111
E-mail: kobelco@rogers-machinery.com
www.knw-series.com